

"SIMPLE" DOCKING STRUCTURE ALLOWANCES:

LAKES OVER 1,000 ACRES:

Average Frontage (Shoreline Avg. With Straight Line)	Dock Surface Area Allowed Square Feet	Accessory Impacts Area Allowed Square Feet	Total Area of Use Allowed Square Feet	Min. Deck Width	Max. Deck Width	Allowed Max. Std. Dock Length	Max. Boatlifts Allowed	Max. PWC Lifts Allowed	Max. Canopies Allowed
Frontage < 75	96	0	96	4	6	24	0	0	0
75 Frontage < 150	300	600	900	4	10	50	2	2	1
150 Frontage < 225	500	900	1400	4	10	50	3	3	2
225 Frontage < 300	700	1200	1900	4	10	50	4	4	3
300 + ft Frontage	900	1400	2300	4	10	50	5	5	4

min } as it
 minor } stands
 major } now

Legal Boatslip Definition: 8 ft x 25 ft x 3 ft (200 sq ft)

Should be 2000 max
 b/c mitigation

INTERNAL NOTES:

Min. Frontage	After Setbacks Usable Lin. Ft.	Std. Allow. Dock Length Total Usable Water Area	Percent. Allowed Impounded Area
50	10	240	40%
75	35	1,750	51%
150	110	5,500	25%
225	185	9,250	21%
300	260	13,000	18%

LAKES UNDER 1,000 ACRES:

Average Frontage (Shoreline Avg. With Straight Line)	Dock Surface Area Allowed Square Feet	Accessory Impacts Area Allowed Square Feet	Total Area of Use Allowed Square Feet	Min. Deck Width	Max. Deck Width	Allowed Max. Std. Dock Length	Max. Boatlifts Allowed	Max. PWC Lifts Allowed	Max. Canopies Allowed
Frontage < 75	96	0	96	4	6	24	0	0	0
75 Frontage < 150	225	450	675	4	10	50	1	1	0
150 Frontage < 225	375	675	1050	4	10	50	2	2	1
225 Frontage < 300	525	900	1425	4	10	50	3	3	2
300 + ft Frontage	675	1050	1725	4	10	50	4	4	3

Legal Boatslip Definition: 6 ft x 20 ft x 3 ft (120 sq ft)

INTERNAL NOTES:

Min. Frontage	After Setbacks Usable Lin. Ft.	Std. Allow. Dock Length Total Usable Water Area	Percent. Allowed Impounded Area
50	10	240	40%
75	35	1,750	39%
150	110	5,500	19%
225	185	9,250	15%
300	260	13,000	13%